



# Ready Go!

Fabric by Richard Neuman Pattern Design by September Olson 60" x 68"

## **Materials**

Yardages based on 42" wide *unwashed* fabric. Prewashing fabric may require additional yardage.

1 ¼ yds Blue Car Toile (Y0879-30) (border)

5/8 yd Med Blue Car Toss (Y0881-30) 5/8 yd Dk Blue Car Toss (Y0881-31) 5/8 yd Orange Equip. Toss (Y0882-36)

5/8 yd Red Sm Cross (Y0883-4) 5/8 yd Dk Blue Sm Cross (Y0883-31)

3/4 yd Black Sm Cross (Y0883-3)

1/4 yd Red Tracks (Y0880-4)

3/4 yd Yellow Tracks (Y0880-9) (inc binding)

1/4 yd Green Tracks (Y0880-21) 3/8 yd Blue Tracks (Y0880-31) (border)

3 3/4 yds Backing of choice

# **Cut the Fabrics**

WOF = Width of Fabric LOF = Length of Fabric

#### From Blue Car Toile cut:

 $7 - 5\frac{1}{2}$  wide x WOF strips

#### From Medium Blue Car Toss cut:

 $8-8\frac{1}{2}$ " squares

## From Dark Blue Car Toss cut:

5 – 81/2" squares

 $2 - 2\frac{1}{2}$ " x  $8\frac{1}{2}$ " rectangle

# From Orange Equipment Toss cut:

 $6 - 8\frac{1}{2}$ " squares

 $1 - 2\frac{1}{2}$ " x  $8\frac{1}{2}$ " rectangle

#### From Red Sm Cross cut:

 $5 - 8\frac{1}{2}$ " squares

 $2 - 2\frac{1}{2}$ " x  $8\frac{1}{2}$ " rectangles

### From Dark Blue Sm Cross cut:

 $6 - 8\frac{1}{2}$ " squares

1-21/2" x 81/2" rectangle

## From Black Sm Cross cut:

- $4 1\frac{1}{2}$ " x  $21\frac{1}{2}$ " rectangles
- $4 2'' \times 8\frac{1}{2}$ " rectangles
- $4 2'' \times 6\frac{1}{2}$ " rectangles
- $6 1\frac{1}{2}$ " x  $14\frac{1}{2}$ " rectangles
- $6 1\frac{1}{2}$ " x  $6\frac{1}{2}$ " rectangles
- 6 1½" x 4½" rectangles

24 – 2" squares

36 – 11/2" squares

## From Red Tracks cut:

 $2-6\frac{1}{2}$ " squares

 $3 - 4\frac{1}{2}$ " squares

# From Yellow Tracks cut:

 $7 - 2\frac{1}{2}$ " wide x WOF strips (binding)

2-61/2'' squares

 $3 - 4\frac{1}{2}$ " squares

## From Green Tracks cut:

 $2 - 6\frac{1}{2}$ " squares

 $3 - 4\frac{1}{2}$ " squares

#### From Blue Tracks cut:

 $6 - 1\frac{1}{2}$  wide x WOF strips

# **Directions**

Prior to starting this project, please check our web site for any updates: www.clothworks.com.

#### Making the Stoplights

- 1. Pencil a diagonal line from one corner to the opposite corner on the back of the 2" black cross squares (figure 1).
- 2. Place one black cross square right sides facing on a red tracks 6½" square (figure 2). Sew on the line and trim the selvage to ¼". Repeat to sew a black tracks square to all four corners of the red tracks square. Press the corners open. Repeat with the rest of the red, green and yellow tracks 6½" squares.
- 3. Sew into a row a red tracks square unit, a 2" x 6½" black cross rectangle, a yellow tracks unit, a 2" x 6½" black cross rectangle and a green tracks unit (figure 3). Press the seam allowance towards the dark fabric.
- 4. Sew a black cross  $1\frac{1}{2}$ " x  $21\frac{1}{2}$ " rectangle to the left and right sides of the stoplight center and press the seam allowance outward.
- 5. Sew a black cross 2" x 8½" rectangle to the top and bottom of the stoplight center and press the seam allowance outward. Repeat to make 2 stop lights that measure 8½" x 24½".
- 6. Repeat to make 3 smaller stop lights with the 4 ½" red, yellow and green tracks squares and 1 ½" black cross squares and rectangles.
- 7. Sew end to end a 2½" x 8½" dark blue car toss rectangle and a 2½" x 8½" red cross rectangle and press the seam allowance towards the blue fabric (figure 4). Sew the unit to the left side of one of the small stoplights and press the seam allowance towards the black fabric. Repeat to sew the red cross/orange equipment toss unit and the blue cross/dark blue car toss unit together and to the right sides of the remaining small stoplights (see quilt picture).





Figure 2



Figure 3

# **Sewing the Center Together**

1. Layout the colored 8½" squares and large and small stoplights as shown in the quilt picture. Sew the patches into vertical rows. Sew the rows together and press the quilt top.

## **Adding the Borders**

- 1. Measure the length of the quilt center and piece and trim two borders from the blue tracks 1½" wide x WOF strips. Sew the borders to the left and right sides of the quilt center and press the seam allowances to the outside.
- 2. Measure the width of the quilt and piece and trim two borders from the remaining blue tracks strips. Sew to the top and bottom sides and press the seam allowances to the outside.
- 3. Repeat to add the outside border with the 5½" wide x WOF blue car toile strips and press the seam allowances to the outside.

#### Finishing the Quilt

- 1. Layer, baste and quilt as desired. Trim off the excess backing and batting from around the outside border.
- 2. Make the binding strip from the 2½" wide x WOF yellow tracks strips and apply to the quilt.




Figure 4




Figure 5

While every attempt has been made to give accurate measurements, yardage requirements, and construction directions, this does not allow for personal variations in measuring, cutting and/or sewing. Clothworks is not responsible for printing errors.